

BASIC BELTED HARNESS

FA1351G



20C/Basic Harness (SC2)

- **Application:** Fall arrest
- **Attachment:** Dorsal position (for fall arrest)
- **Features:** Easy to fit harness; Lightweight;
- **Lanyard set:** Single leg lanyard with scaffold hook
Energy absorbing element 1.75m long (including energy absorber)
- **Adjustment:** Leg straps (standard buckles) Chest strap (25mm dee rings)
- **Sizing:** Small, medium, large, XL and 2XL
- **Options:** grange Harness Step can be fitted (not supplied standard) Can be supplied with a 45mm chest strap

FEATURES:

- **Primary webbing:** Polyester 44mm wide with breaking strength of 22kN
- **Steel dee ring:** Breaking strength of 3 ton
- **Standard buckle:** Alloy steel 2/3 bar buckle to suit 44mm webbing
- **Plastic insert:** Polypropylene molded insert
- **Hook:** Steel double action snap hook with breaking strength of 22kN
- **Tear webbing:** Polyester 44mm wide manufactured to perform to SANS 50355:2003 Energy absorbers
- **Heat shrink:** Clear plastic sleeve 67mm
- **Yarn:** Polyester thread with colour contrasting to webbing colour
- **Chest strap webbing:** Polyester 25mm wide
- **Chest strap buckle:** Alloy steel dee ring to suit 25mm webbing
- **Label:** Textile material 40mm wide with thermal transfer